

H 8 0 0 × W 1 0 0 0 (直忍付) S=1:20

Technical drawing of a cross-section of a building's exterior wall and foundation. The drawing shows a concrete wall with a width of 1000mm. The wall is reinforced with horizontal and vertical bars. The horizontal bars are labeled "バーブドワイヤ $\phi 2.0$ " and "胴縁 $t=2.3$ ". The vertical bars are labeled "Wメッシュ" and " $\phi 50.8 \times 1.6$ ". The wall is supported by a foundation with a width of 300mm. The foundation is labeled " $\phi 60.5 \times 2.3$ " and "胴縁 $t=2.3$ ". The drawing also shows a "戸当り付両面回転施錠" (door stop and double-sided rotating lock) and a "蝶番" (hinge). The total height of the wall is 800mm, with a section of 450mm and another of 760mm. The foundation height is 250mm. The ground level is marked as "▽GL+0m".

Technical drawing of a rectangular plate. The plate has a width of 45 and a height of 125. There are two holes, each with a diameter of $\phi 3.6$. The holes are positioned symmetrically along the vertical centerline. The distance between the centers of the two holes is 125. The distance from the center of each hole to the nearest vertical edge is 45.

- ・施錠門柱の扉開き側に障害物（兼用フェンス、壁など）を有する場合には、両面回転施錠の戸当りが障害物と干渉するため、開き方向の変更が必要である。